

# SPECTRO LUBRICANT TECHNICAL DATA

## Spectro Golden Gear Lubricant



### Description

Spectro Golden Gear Lubricant is a shear-stable petroleum engine case lubricant designed to withstand the punishment of second and third gear starts. Special polymers provide exceptional clutch engagement and temperature stability

Meets all known OEM warranty requirements.

### Application

For use in all modern 2-cycle motocross machine engine/clutch cases where SAE 10w30 or SAE 10w40 SE/SF/SG or 80w lubricants are recommended.

### For Racing Use

Change frequently, preferably every race weekend.

### Typical Inspections

	80W
Kinematic Viscosity @ 100° C cST	9.6
Kinematic Viscosity @ 40° C cST	60.3
Flash Point, °C	216
Pourpoint, °C	-27
Viscosity Index	143

Code	Description	Weight
L.GSCGL80	12/1 Liter Bottles	26 Lbs.
L.GSCGL85	12/1 Liter Bottles	26 Lbs.

- MEETS ALL KNOWN MOTORCYCLE MANUFACTURER'S WARRANTY REQUIREMENTS AND RECOMMENDATIONS.
- FOR USE IN ALL TWO-STROKE TRANSMISSIONS AND SEPARATE TRANSMISSIONS.
- LOW DRAG, LOW FRICTION LOSS SAE 80W (10W30) AND 85W(10W40) VISCOSITY
- ELIMINATES CLUTCH 'DRAG AND "SLIPPING." EXCELLENT FOR 2ND AND 3RD GEAR STARTS.
- A.P.I. GL-4

SPECTRO OILS OF AMERICA  
993 Federal Rd., Brookfield, CT 06804  
203-775-1291 Fax 203-775-8720  
[www.spectro-oils.com](http://www.spectro-oils.com)

