

SPECTRO LUBRICANT TECHNICAL DATA

Platinum 4 Full Synthetic Lubricant



- FULL SYNTHETIC FORMULATION REDUCES INTERNAL FRICTION AT ALL TEMPERATURES AND WILL INCREASE HORSEPOWER.
- EXTENDS COMPONENT LIFE.
- EASIER, SMOOTHER SHIFTING.
- TREMENDOUS LUBRICATION PROTECTION IN EXTREME HEAT OR COLD CONDITIONS.
- API SG/SH/SL/JASO MA, MA2

Description

Platinum Full Synthetic is the ultimate synthetic engine lubricant. Exceeds all known motorcycle manufacturer's warranty requirements, plus A.P.I. SG/SH/SL/JASO MA and MA2. Smoother shifting, reduced friction, increased horsepower, highest shear stability. Breakthrough additives technology provides a reduction in drag and friction loss and extends engine component life. For street or track. Meets all known OEM warranty requirements.

Application

Platinum 4 Full Synthetic Oil is formulated specifically for use in all racing and high performance and demanding applications, especially high heat or extreme cold.

For Racing Use

Platinum 4 Full Synthetic Oil should be used at the manufacturers' recommended change interval. Otherwise, adhere to the "change frequently" rule. No special steps need to be taken when switching to a full synthetic.

Typical Inspections

	5w40	10w40	10w50	15w50
Kinematic Viscosity @ 100° C cST	14.4	13.8	17.2	17.2
Kinematic Viscosity @ 40° C cST	96.0	89.5	138	138
Flash Point, °C	236	230	245	245
Pourpoint, °C	-48	-40	-45	-42
Viscosity Index	155	159	136	151

Code

L.SP454
L.SP414
L.SP4105
L.SP4155

Description

12/1 liter bottles
12/1 liter bottles
12/1 liter bottles
12/1 liter bottles

Weight

26 Lbs.
26 Lbs.
26 Lbs.
26 Lbs.

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

