

SPECTRO LUBRICANT TECHNICAL DATA

Platinum Full Synthetic Transmission Oil



- ENERGY EFFICIENT, LOW DRAG FORMULA DRAMATICALLY REDUCES DRAG AT ALL TEMPERATURES.
- REDUCES WEAR.
- EXTENDS COMPONENT LIFE.
- PROVIDES EASIER, SMOOTHER SHIFTING.
- SIGNIFICANTLY LOWERS GEAR NOISE.
- TREMENDOUS LUBRICATION PROTECTION IN EXTREME HEAT OR COLD CONDITIONS.
- EXCEPTIONAL OXIDATION STABILITY.

Description

Platinum Full Synthetic Transmission Oil is the ultimate gear oil for use in high performance transmissions. It is crafted of select Group IV PAO base synthetics with optimum additive packages for the ultimate lubrication protection and to dramatically reduce drag at all temperature ranges, provide exceptional oxidation stability, and provide total protection to gears and bearings. Recommended for applications calling for GL-1 lubricants. Dyed lime green. The SAE 75w140 formulation eases shifting when cold. High loads and extreme heat do not affect the oil, so it performs well when pushed hard and long. A.P.I. GL-1 rated.

Meets all known OEM warranty requirements.

Application

Spectro Platinum Transmission oil should be used according to the manufacturer's recommended specifications. No special steps need to be taken when switching to Spectro Platinum full synthetic lubricants.

Typical Inspections	75w90	75w140
API Gravity	31.3	31.0
Kinematic Viscosity @ 100° C cST	15.8	24.8
Kinematic Viscosity @ 40° C cST	100	182
Flash Point, °C	200	208
Pourpoint, °C	-48	-46
Viscosity Index	172	174

Code	Description	Weight
L.75w901	12/1 Liter Bottles	26 Lbs.
L.75w1401	12/1 Liter Bottles	26 Lbs.

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

